


| | |
|---|---------------------------|
|  | Page: 1 |
| SAFETY DATA SHEET | Revision Date: 07/31/2016 |
| | Print Date: 6/20/2017 |
| | SDS Number: R0524201 |
| Valvoline™ S.T.O.U. SAE 10W/30 INDUSTRIAL OIL VE17018 | Version: 1.1 |

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ S.T.O.U. SAE 10W/30
INDUSTRIAL OIL

Recommended use of the chemical and restrictions on use

Use of the Substance/Mixture : Lubricating oils

| | |
|---|--|
| Details of the supplier of the safety data sheet Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America SDS@valvoline.com | Emergency telephone number 1-800-VALVOLINE Regulatory Information Number 1-800-TEAMVAL Product Information 1-800-TEAMVAL |
|---|--|

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.


SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components


| Chemical Name | CAS-No. | Classification | Concentration (%) |
|--------------------|------------|-------------------|-------------------|
| HYDROTREATED LIGHT | 64742-55-8 | Asp. Tox. 1; H304 | 42.99 |

| | |
|--|---------------------------|
|  | Page: 2 |
| SAFETY DATA SHEET | Revision Date: 07/31/2016 |
| | Print Date: 6/20/2017 |
| | SDS Number: R0524201 |
| Valvoline™ S.T.O.U. SAE 10W/30 INDUSTRIAL OIL VE17018 | Version: 1.1 |

| | | | |
|------------------------------|------------|--|------|
| PARAFFINIC DISTILLATE | | | |
| MINERAL OIL | | Not a hazardous substance or mixture. | 7.79 |
| ZINC DIALKYL DITHIOPHOSPHATE | 68649-42-3 | Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 2; H411 | 1.28 |

SECTION 4. FIRST AID MEASURES

| | |
|---|--|
| General advice | : No hazards which require special first aid measures. |
| If inhaled | : If breathed in, move person into fresh air. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician. |
| In case of skin contact | : Remove contaminated clothing. If irritation develops, get medical attention. If on skin, rinse well with water. Wash contaminated clothing before re-use. |
| In case of eye contact | : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist. |
| If swallowed | : Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. |
| Most important symptoms and effects, both acute and delayed | : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum |

| | | |
|---|--|---------------------------|
|  | | Page: 3 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 6/20/2017 |
| | | SDS Number: R0524201 |
| Valvoline™ S.T.O.U. SAE 10W/30 INDUSTRIAL OIL VE17018 | | Version: 1.1 |

occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons

Specific extinguishing methods :


Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and : Use personal protective equipment.
Persons not wearing protective equipment should be excluded

| | | |
|---|--|---------------------------|
|  | | Page: 4 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 6/20/2017 |
| | | SDS Number: R0524201 |
| Valvoline™ S.T.O.U. SAE 10W/30 INDUSTRIAL OIL VE17018 | | Version: 1.1 |

emergency procedures : from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE


Advice on safe handling : Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---|------------|----------------------------------|---|-----------------|
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE | 64742-55-8 | REL | 5 mg/m3 Mist. | NIOSH/GUID E |
| | | STEL | 10 mg/m3 Mist. | NIOSH/GUID E |
| | | PEL | 5 mg/m3 Mist. | OSHA_TRA NS |
| MINERAL OIL | | REL | 5 mg/m3 Mist. | NIOSH/GUID E |
| | | STEL | 10 mg/m3 Mist. | NIOSH/GUID E |
| | | PEL | 5 mg/m3 Mist. | OSHA_TRA NS |
| | | TWA | 5 mg/m3 Mist. | TN OEL |
| | | TWA | 5 mg/m3 Inhalable fraction. | ACGIH |

| | |
|---|---------------------------|
|  | Page: 5 |
| SAFETY DATA SHEET | Revision Date: 07/31/2016 |
| | Print Date: 6/20/2017 |
| | SDS Number: R0524201 |
| Valvoline™ S.T.O.U. SAE 10W/30 INDUSTRIAL OIL VE17018 | Version: 1.1 |

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : amber

Odour : liquid

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : <-27 °F / -33 °C


Boiling point/boiling range : > 437.00 °F / 225.00 °C

Flash point : 381 °F / 194 °C
Method: Pensky Martens closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available


Upper explosion limit : No data available

| | | |
|---|--|---------------------------|
|  | | Page: 6 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 6/20/2017 |
| | | SDS Number: R0524201 |
| Valvoline™ S.T.O.U. SAE 10W/30 INDUSTRIAL OIL VE17018 | | Version: 1.1 |

| | |
|--|---|
| Lower explosion limit | : No data available |
| Vapour pressure | : No data available |
| Relative vapour density | : No data available |
| Relative density | : ca. 0.872 (15.6 °C) |
| Density | : ca. 0.872 g/cm ³ (15.6 °C) |
| Bulk density | : Not applicable |
| Solubility(ies) | |
| Water solubility | : partly miscible |
| Solubility in other solvents | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Thermal decomposition | : No data available |
| Viscosity | |
| Viscosity, dynamic | : No data available |
| Viscosity, kinematic | : ca. 10.50 mm ² /s (100 °C) |
| | ca. 69 mm ² /s (40 °C) |
| Oxidizing properties | : No data available |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| Reactivity | : No decomposition if stored and applied as directed. |
| Chemical stability | : Stable under recommended storage conditions. |
| Possibility of hazardous reactions | : Product will not undergo hazardous polymerization. |
| Conditions to avoid | : excessive heat |
| Incompatible materials | : Strong oxidizing agents |
| Hazardous decomposition products | carbon dioxide and carbon monoxide Hydrocarbons |

| | | |
|---|--|---------------------------|
|  | | Page: 7 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 6/20/2017 |
| | | SDS Number: R0524201 |
| Valvoline™ S.T.O.U. SAE 10W/30 INDUSTRIAL OIL VE17018 | | Version: 1.1 |

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

ZINC DIALKYL DITHIOPHOSPHATE:

Acute oral toxicity : LD 50 (Rat): > 2,000 - 5,000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to skin

MINERAL OIL:

Result: Mildly irritating to skin

ZINC DIALKYL DITHIOPHOSPHATE:

Result: Irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result: Slightly irritating to eyes

Remarks: Expected based on components.

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:


Result: Mildly irritating to eyes

MINERAL OIL:

Result: Mildly irritating to eyes

ZINC DIALKYL DITHIOPHOSPHATE:

Result: Corrosive to eyes

| | | |
|---|--|---------------------------|
|  | | Page: 8 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 6/20/2017 |
| | | SDS Number: R0524201 |
| Valvoline™ S.T.O.U. SAE 10W/30 INDUSTRIAL OIL VE17018 | | Version: 1.1 |

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity


No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

| | | |
|---|--|---------------------------|
|  | | Page: 9 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 6/20/2017 |
| | | SDS Number: R0524201 |
| Valvoline™ S.T.O.U. SAE 10W30 INDUSTRIAL OIL VE17018 | | Version: 1.1 |

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

| ID NUMBER | PROPER SHIPPING NAME | *HAZARD CLASS | SUBSIDIARY HAZARDS | PACKING GROUP | MARINE POLLUTANT / LTD. QTY. |
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|
| | | | | | |

U.S. DOT - ROAD

| |
|---------------------|
| Not dangerous goods |
| |

CFR_RAIL_C


| |
|---------------------|
| Not dangerous goods |
| |

U.S. DOT - INLAND WATERWAYS

| |
|---------------------|
| Not dangerous goods |
| |

TDG_ROAD_C

| |
|---------------------|
| Not dangerous goods |
|---------------------|

| | | |
|---|--|---------------------------|
|  | | Page: 10 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 6/20/2017 |
| | | SDS Number: R0524201 |
| Valvoline™ S.T.O.U. SAE 10W30 INDUSTRIAL OIL | | Version: 1.1 |
| VE17018 | | |

TDG_RAIL_C

| |
|---------------------|
| Not dangerous goods |
| |

TDG_INWT_C

| |
|---------------------|
| Not dangerous goods |
| |

INTERNATIONAL MARITIME DANGEROUS GOODS

| | |
|---------------------|--|
| Not dangerous goods | MARINE POLLUTANT:(ZINC DIALKYL DITHIOPHOS PHATE, PHENOL, 4- DODECYL-) |
| | |

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

| |
|---------------------|
| Not dangerous goods |
| |

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

| |
|---------------------|
| Not dangerous goods |
| |

MX_DG

| |
|---------------------|
| Not dangerous goods |
| |

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

| | |
|------------------|-----|
| Marine pollutant | yes |
|------------------|-----|

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION


SARA 311/312 Hazards : No SARA Hazards

SARA 313 Component(s)

ZINC DIALKYL
DITHIOPHOSPHATE

68649-42-3

1.28 %

| | |
|---|---------------------------|
|  | Page: 11 |
| SAFETY DATA SHEET | Revision Date: 07/31/2016 |
| | Print Date: 6/20/2017 |
| | SDS Number: R0524201 |
| Valvoline™ S.T.O.U. SAE 10W/30 INDUSTRIAL OIL VE17018 | Version: 1.1 |

California Prop 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

| | |
|-------|---|
| TSCA | : On TSCA Inventory |
| DSL | : All components of this product are on the Canadian DSL. |
| AUSTR | : On the inventory, or in compliance with the inventory |
| ENCS | : Not in compliance with the inventory |
| KECL | : On the inventory, or in compliance with the inventory |
| PICCS | : On the inventory, or in compliance with the inventory |
| IECSC | : On the inventory, or in compliance with the inventory |


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information


Revision Date: 07/31/2016

| NFPA: | HMIS III: | | | | | | |
|---|--|---------------|--|---------------------|--|------------------------|--|
| <p>Flammability</p>  <p>Health</p> <p>Instability</p> <p>Special hazard.</p> | <table border="1"> <tr> <td data-bbox="845 1444 1212 1512">HEALTH</td><td data-bbox="1212 1444 1332 1512"></td></tr> <tr> <td data-bbox="845 1512 1212 1579">FLAMMABILITY</td><td data-bbox="1212 1512 1332 1579"></td></tr> <tr> <td data-bbox="845 1579 1212 1646">PHYSICAL HAZARD</td><td data-bbox="1212 1579 1332 1646"></td></tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p> | HEALTH | | FLAMMABILITY | | PHYSICAL HAZARD | |
| HEALTH | | | | | | | |
| FLAMMABILITY | | | | | | | |
| PHYSICAL HAZARD | | | | | | | |

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

| | |
|---|---------------------------|
|  | Page: 12 |
| SAFETY DATA SHEET | Revision Date: 07/31/2016 |
| | Print Date: 6/20/2017 |
| | SDS Number: R0524201 |
| Valvoline™ S.T.O.U. SAE 10W/30 INDUSTRIAL OIL VE17018 | Version: 1.1 |

| | |
|------|--|
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H411 | Toxic to aquatic life with long lasting effects. |

Further information

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit


STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

| | | |
|---|--|---------------------------|
|  | | Page: 13 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 6/20/2017 |
| | | SDS Number: R0524201 |
| Valvoline™ S.T.O.U. SAE 10W/30 INDUSTRIAL OIL VE17018 | | Version: 1.1 |

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System